

## WEV 15-125 HT (600562420) Angle grinder (110-120 V / 60 Hz); Cardboard box; with speed control

Order no. 600562420  
EAN 4007430245892



Product may differ from Image



- Optimum processing of stone: robust, powerful angle grinder with gear reduction and reduced, adjustable speed for material-friendly working
- Longer service life, more power: the Metabo Longlife-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

Disc-Ø	125 mm // 5 "
Rated input power	1550 W
Output power	900 W
No-load speed	2800 - 9600 rpm
Speed at rated load	9600 rpm
Torque	4.2 Nm / 37 in-lbs
Spindle thread	5/8" - 11 UNC
Handle circumference	206 mm / 8 1/8 "
Weight (without power cable)	2.5 kg / 5.5 lbs
Cable length	2.5 m / 8 ft

### Vibration

Surface grinding	5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Polishing	2.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
 Quick-locking nut  
 Side handle  
 Inner support flange  
 Nut with two holes